

Amendments to the Claims:

1. (Currently Amended) An apparatus adapted to examine a length of a cigarette paper comprising a pattern including a first band and a second band, the pattern repeating along the length thereof, the apparatus comprising:

- a second bobbin configured to be capable of receiving the cigarette paper and to have the cigarette paper advanced thereto and wound thereon after the cigarette paper is unwound from a first bobbin;
- a pattern detection device disposed between the first and second bobbins and configured to receive the cigarette paper unwound from the first bobbin, the pattern detection device being configured to detect at least one of the bands and produce a signal in response thereto; and
- a testing device in communication with the pattern detection device and disposed serially therewith between the first and second bobbins, the testing device being configured to nondestructively ~~determine a material property~~ measure at least one of a porosity and a basis weight of at least one of the bands in contemporaneous response to the signal, while the cigarette paper is between the first and second bobbins and before the cigarette paper is wound on the second bobbin.

2. (Currently Amended) An apparatus according to Claim 1 wherein the second bobbin is responsive to the signal to selectively stop advancement of the cigarette paper to the second bobbin and the testing device is contemporaneously responsive to the signal to ~~determine the property~~ nondestructively measure at least one of the porosity and the basis weight of the at least one of the bands when advancement of the cigarette paper is stopped.

3. (Original) An apparatus according to Claim 1 wherein the second bobbin is adapted to be received by a cigarette manufacturing machine such that the cigarette paper wound thereon can be used to manufacture a cigarette.

4. (Cancelled)

5. (Original) An apparatus according to Claim 1 further comprising a drive system capable of being operably engaged with the second bobbin so as to wind the cigarette paper thereon, the drive system being operably engaged with the pattern detection device and responsive thereto so as to allow selective advancement of the cigarette paper onto the second bobbin.

6. (Original) An apparatus according to Claim 1 further comprising a brake system operably engaged with the first bobbin and configured to cooperate therewith so as to maintain a tension on the cigarette paper between the first bobbin and the second bobbin.

7. (Original) An apparatus according to Claim 1 further comprising a paper-engaging member configured to operably engage the cigarette paper between the first and second bobbins so as to maintain a tension on the cigarette paper.

8. (Currently Amended) An apparatus according to Claim 1 further comprising a controller in communication with the pattern detection device and the testing device, the controller being configured to control advancement of the cigarette paper onto the second bobbin in response to the signal from the pattern detection device and to direct the testing device to ~~determine the property~~ nondestructively measure at least one of the porosity and the basis weight of the cigarette paper in direct response to the signal.

9. (Original) An apparatus according to Claim 1 wherein the first bobbin is interchangeable with the second bobbin.

10. (Currently Amended) A system for examining a cigarette paper and manufacturing a cigarette therefrom, the system comprising:

a cigarette manufacturing device configured to manufacture the cigarette from a length of

the cigarette paper, the cigarette paper having a pattern including a first band and a second band, with the pattern repeating along the length thereof; and
a cigarette paper testing apparatus adapted to ~~determine a property of~~ test one of the bands of the cigarette paper before the cigarette paper is used to manufacture the cigarette, the cigarette paper testing apparatus comprising:
a second bobbin configured to be capable of receiving the cigarette paper and to have the cigarette paper advanced thereto and wound thereon after the cigarette paper is unwound from a first bobbin, the second bobbin being configured to be received by the cigarette manufacturing apparatus so as to provide the cigarette paper thereto;
a pattern detection device disposed between the first and second bobbins and configured to receive the cigarette paper unwound from the first bobbin, the pattern detection device being configured to detect at least one of the bands and produce a band detection signal in response thereto; and
a testing device in communication with the pattern detection device and disposed serially therewith between the first and second bobbins, the testing device being configured to nondestructively ~~determine a material property~~ measure at least one of a porosity and a basis weight of at least one of the bands in contemporaneous response to the band detection signal, while the cigarette paper is between the first and second bobbins and before the cigarette paper is wound on the second bobbin.

11. (Currently Amended) A system according to Claim 10 wherein the second bobbin is responsive to the band detection signal to selectively stop advancement of the cigarette paper to the second bobbin and the testing device is contemporaneously responsive to the band detection signal to ~~determine the property~~ nondestructively measure at least one of the porosity and the basis weight of the at least one of the bands when advancement of the cigarette paper is stopped.

12. (Original) A system according to Claim 10 wherein the first bobbin is interchangeable

with the second bobbin.

13. (Cancelled)

14. (Original) A system according to Claim 10 further comprising a drive system capable of being operably engaged with the second bobbin so as to wind the cigarette paper thereon, the drive system being operably engaged with the pattern detection device and responsive thereto so as to allow selective advancement of the cigarette paper onto the second bobbin.

15. (Original) A system according to Claim 10 further comprising a brake system operably engaged with the first bobbin and configured to cooperate therewith so as to maintain a tension on the cigarette paper between the first bobbin and the second bobbin.

16. (Original) A system according to Claim 10 further comprising a paper-engaging member configured to operably engage the cigarette paper between the first and second bobbins so as to maintain a tension on the cigarette paper.

17. (Currently Amended) A system according to Claim 10 further comprising a controller in communication with the pattern detection device and the testing device, the controller being configured to control advancement of the cigarette paper onto the second bobbin in response to the band detection signal from the pattern detection device and to direct the testing device to ~~determine the property~~ nondestructively measure at least one of the porosity and the basis weight of the cigarette paper in direct response to the band detection signal.

18. (Currently Amended) A method of examining a length of a cigarette paper having a pattern including a first band and a second band, the pattern repeating along the length thereof, said method comprising:

detecting at least one of the bands with a pattern detection device disposed between the
first and second bobbins as the cigarette paper is advanced to and wound on the

second bobbin after being unwound from the first bobbin;
producing a band detection signal with the pattern detection device in response to the
detection of the at least one of the bands; and
nondestructively ~~determining a material property~~ measuring at least one of a porosity and
a basis weight of at least one of the bands with a testing device in communication
with the pattern detection device and disposed serially therewith between the first
and second bobbins, in contemporaneous response to the band detection signal,
while the cigarette paper is between the first and second bobbins and before the
cigarette paper is wound on the second bobbin.

19. (Currently Amended) A method according to Claim 18 further comprising selectively
stopping advancement of the cigarette paper to the second bobbin in response to the band
detection signal and, in contemporaneous response to the band detection signal, determining the
property nondestructively measuring at least one of the porosity and the basis weight of the at
least one of the bands when advancement of the cigarette paper is stopped.

20-21. (Cancelled)

22. (Original) A method according to Claim 18 further comprising selectively advancing
the cigarette paper onto the second bobbin with a drive system operably engaged therewith, the
drive system being operably engaged with the pattern detection device and responsive thereto so
as to determine the selective advancement of the cigarette paper.

23. (Original) A method according to Claim 18 further comprising maintaining a tension
on the cigarette paper between the first bobbin and the second bobbin with a brake system
operably engaged and cooperable with the first bobbin.

24. (Original) A method according to Claim 18 further comprising maintaining a tension
on the cigarette paper with a paper-engaging member configured to operably engage the cigarette

paper between the first and second bobbins.

25. (Currently Amended) A method according to Claim 18 further comprising controlling advancement of the cigarette paper onto the second bobbin, in response to the band detection signal from the pattern detection device, with a controller in communication with the pattern detection device and the testing device.

26. (Currently Amended) A method according to Claim 18 wherein nondestructively determining a property further comprises directing the testing device to nondestructively ~~determine the property~~ nondestructively measure at least one of the porosity and the basis weight of the cigarette paper, in direct response to the band detection signal, with a controller in communication with the pattern detection device and the testing device.

27. (Original) A method according to Claim 18 further comprising removing the second bobbin and replacing the second bobbin with the first bobbin.

28. (Currently Amended) An apparatus adapted to examine a length of a cigarette paper having opposed ends and comprising a pattern including a first band and a second band, the pattern repeating along the length thereof, the apparatus comprising:

- a driven roller device configured to receive one of the ends and to advance the length of the cigarette paper in a machine direction;
- a tension device configured to operably engage the cigarette paper prior to the driven roller device, with respect to the machine direction, and to cooperate with the driven roller device so as to maintain a tension on the cigarette paper therebetween;
- a pattern detection device disposed between the driven roller device and the tension device, the pattern detection device being configured to receive the cigarette paper, to detect at least one of the bands, and to produce a band detection signal in response thereto; and

a testing device in communication with the pattern detection device and disposed serially therewith between the driven roller device and the tension device, the testing device being configured to nondestructively ~~determine a material property~~ measure at least one of a porosity and a basis weight of at least one of the bands in contemporaneous response to the band detection signal.

29. (Currently Amended) An apparatus according to Claim 28 wherein the driven roller device is responsive to the band detection signal to selectively stop advancement of the cigarette paper and the testing device is contemporaneously responsive to the band detection signal to ~~determine the property~~ nondestructively measure at least one of the porosity and the basis weight of the at least one of the bands.

30. (Cancelled)

31. (Currently Amended) An apparatus according to Claim 28 further comprising a controller in communication with the pattern detection device and the testing device, the controller being configured to control advancement of the cigarette paper by the driven roller device in response to the band detection signal from the pattern detection device and to direct the testing device to ~~determine the property~~ nondestructively measure at least one of the porosity and the basis weight of the cigarette paper in direct response to the band detection signal.